

Cordless Impact Driver DTD153



High Performance with Brushless DC Motor.

Max tightening torque

170_{N·m}

Lightweight at

1.3kg







Aluminum hammer case

creates impression of rigidity.

(For some countries only) No need to pull bit sleeve for bit

Twin LED Job light with pre-glow and afterglow

installation

functions





Variable speed control by trigger

Ergonomically designed handle with soft grip

provides comfortable grip and more control while minimizing hand fatigue and pain.

Powered by

18V Li-ion batteries

3,4

High rotational speed

Option

Tool catcher set

enables to hook the machine quickly on a snap hook of waist belt.







Battery Protector

designed to protect the battery cartridge from dust and dripping water in outdoor applications or harsh environments.



Part No. 195798-3

■ Battery / Charger





BL1860B (6.0Ah) BL1850B (5.0Ah) BL1840B (4.0Ah) BL1830B (3.0Ah) BL1820B (2.0Ah) *BL1815N (1.5Ah)

Belt clip



Charger DC18SD



Cordless Impact Driver

DTD153

Wariable Speed







Carrying Case

M4 - M8 (5/32" - 5/16") M5 - M16 (3/16" - 5/8") M5 - M14 (3/16" - 9/16") Capacity Machine screw: Standard bolt : High strength bolt: Coarse thread (in length) : 22 - 125mm (7/8" - 4-7/8") Impacts per minute (ipm) No load speed (rpm) 0-3,600 0-3,400 170 N·m (1,500 in·lbs) 13.0 m/s² Max. fastening torque Vibration Level Sound Pressure Level Sound Power Level 96 dB(A) 107 dB(A) Dimensions (L x W x H) Net weight 126x79x238mm (5"x3-1/8"x9-3/8") BL1850B: 1.5kg (3.3lbs) BL1815N: 1.3kg (2.8lbs)

Standard Equipment: Belt Clip, Battery, Fast Charger

weight according to EPTA-Procedure 01/ver.2.1

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan